



## Fume Hood



LED Display



Waterproof Socket



Water&Gas Remote Control



Double Layer  
1.2mm sheet metal surface,  
melamine board inward.

## ADVANTAGE

1. UV lamp for sterilization.
2. Adjustable air speed: 9 levels.
3. Motorized front window, height adjustable.
4. Microprocessor control system, LED display.

## TECHNICAL PARAMETERS

Model	FH1000(A)	FH1200(A)	FH1500(A)	FH1800(A)	
External Size (W*D*H)	1040*800*2200mm	1240*800*2200mm	1540*800*2200mm	1840*800*2200mm	
Internal Size (W*D*H)	820*670*730mm	1020*670*730mm	1320*670*730mm	1620*670*730mm	
Work Surface Height	850mm				
Max Opening	500mm				
Air Velocity	0.3-0.8m/s				
Noise	≤60dB				
Exhaust Duct	PVC, Standard length: 4 meters. Φ300mm				
Pipe Strap	1 pc				
Fluorescent Lamp	14W*1	21W*1	28W*1	36W*1	
UV Lamp	Emission of 253.7 nanometers for most efficient decontamination				
Blower	Built-in centrifugal blower; Speed adjustable				
Front Window	5mm toughened glass; Motorized; Height adjustable				
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz				
Consumption	400W	400W	500W	500W	
Material	Exterior	Cold-rolled steel with anti-bacteria powder coating.			
	Interior	High grade melamine board with good acid and alkali resistance function			
	Work Table	Chemical resistant phenolic resin			
Stand Accessory	UV lamp*2, Fluorescent lamp, Water tap, Gas tap, Water sink, Base cabinet				
	Total load of 2 waterproof sockets: 500W 4 meter PVC exhaust duct, pipe strap				
Optional Accessory	Active carbon filter				
Gross Weight	230kg	270kg	370kg	420kg	
Package	Main Body	1190*990*1690 mm	1390*990*1690 mm	1690*990*1690mm	1990*990*1690mm
	Base Cabinet	1290*990*980mm	1390*990*980mm	1690*970*970mm	1990*990*980mm