

# Mini Dry Bath Incubator

## MINIC Series

The mini dry bath is a micro-processor controlled heating block with heater (heating types) or semiconductor refrigeration (cooling types) technology. It adapts onboard use, smart, light and convenient for movement, suit for any kind of occasions.



### Feature

*Ensure quality, service and development, the pursuit of excellence and persistence!*

1. Unique designed. Smart and light, convenient movement, suit for various occasions.
2. LCD simultaneously display setting and actual time and temperature. Temperature calibration function.
3. Automatic fault detection function with buzzer alarm.
4. 24V DC input power, built-in over-temperature protection device.
5. Various of blocks for optional choice. Convenient for replacement. Easy cleaning and disinfection.



# Mini Dry Bath Incubator

## Parameters

Ensure quality, service and development, the pursuit of excellence and persistence!


Model	MINIC-100	MINIC-100I
Temp. Control Range	-10 ~100 °C	-10 ~100 °C
Temp. Max. Decrease	R.T. decreases 25 °C	R.T. decreases 25 °C
Temp. Setting Range	-10 ~100 °C	-10 ~100 °C
Temp. Stability@100 °C	≤±0.5 °C	≤±0.5 °C
Temp. Stability@40 °C	≤±0.3 °C	≤±0.3 °C
Block Temp. Uniformity	≤±0.3 °C	≤±0.3 °C
Temp. Display Accuracy	0.1 °C	0.1 °C
Heating Speed	≤15min (20 to 100 °C)	≤15min (20 to 100 °C)
Cooling Speed	≤30min (R.T. decrease 20 °C) @R.T. 26 °C	≤30min (R.T. decrease 20 °C) @R.T. 26 °C
Heating Cover	no	with
Time Range	1sec ~999sec or 1min ~1002min	1sec ~999sec or 1min ~1003min
Voltage	DC24V adapter	DC24V adapter
Power	120W	120W
Dimension (WxDxH)	110 x 156 x 103mm	110 x 156 x 108mm
Net Weight	1.4kgs	1.4kgs



# Mini Dry Bath Incubator

## Optional Accessories

Ensure quality, service and development, the pursuit of excellence and persistence!



Cat#	Spec	Dia. of hole	Hole bottom shape	Block dimension
MINI-A	0.2 ml x 40	6.1 mm	Cone bottom	71 x 47 x 32 mm
MINI-B	0.5 ml x 24	8 mm	Cone bottom	71 x 47 x 32 mm
MINI-C	1.5 ml x 15	10.8 mm	Cone bottom	71 x 47 x 32 mm
MINI-D	2.0 ml x 15	10.8 mm	Round bottom	71 x 47 x 32 mm
MINI-E	cuvette x 8	8~12.5 mm (Maximum edge length 15mm)	No bottom	71 x 47 x 32 mm
MINI-F	15ml x 4	16.9mm	Flat bottom	71 x 47 x 82 mm
MINI-G	50 ml x 2	29.2mm	Flat bottom	71 x 47 x 82 mm

**Note: MINI-F / MINI-G is a non-standard module, the insulation cover cannot be closed**

